



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : F41H 5/04	A1	(11) International Publication Number: WO 00/55567 (43) International Publication Date: 21 September 2000 (21.09.00)
(21) International Application Number: PCT/US00/06220 (22) International Filing Date: 10 March 2000 (10.03.00) (30) Priority Data: 60/123,569 10 March 1999 (10.03.99) US (63) Related by Continuation (CON) or Continuation-in-Part (CIP) to Earlier Application US 60/123,569 (CON) Filed on 10 March 1999 (10.03.99) (71) Applicant (for all designated States except US): FRAUNHOFER, USA, INC. [US/US]; 24 Frank Lloyd Wright Drive, Ann Arbor, MI 48106-0335 (US). (72) Inventors; and (75) Inventors/Applicants (for US only): YU, Chin-Jye [-/US]; 9 Abbey Road, Newark, DE 19702 (US). CLAAR, Terry, Dennis [US/US]; 306 Fashion Circle, Newark, DE 19711 (US). EIFERT, Harald, Heinrich [DE/US]; 46 Quail Hollow Drive, Hockessin, DE 19707 (US).		(74) Agents: ROHM, Benita, J. et al.; Rohm & Monsanto, PLC, Suite 1525, 660 Woodward Avenue, Detroit, MI 48226 (US). (81) Designated States: US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: USE OF METAL FOAMS IN ARMOR SYSTEMS		
(57) Abstract		
<p>In a multi-layer armor system (10), useful for military vehicles, a metallic foam is provided as the shock energy-absorbing element. In a typical arrangement, the metallic foam shock-absorbing element (12) is sandwiched between a high strength strike plate (11) and a backing plate (13). Typically, the backing plate is a highly deforming metal, such a titanium, aluminum, or steel. However, the backing plate may comprise one or more layers of metal, ceramic or polymer-based composites. The high strength strike plate may be ceramic or metal. The shock-absorbing element is preferably a closed-cell metal foam with a high porosity that is effective in containing rearward deformation of the strike plate from a projectile strike. In preferred embodiment, the shock-absorbing element is an aluminum foam with a porosity of 80 percent by volume.</p>	<p>The diagram illustrates a cross-section of a multi-layer armor system (10). It consists of three main layers: a high strength strike plate (11) on the left, a metallic foam shock-absorbing element (12) in the center, and a backing plate (13) on the right. The foam element (12) is depicted with a porous, irregular internal structure. The entire assembly is labeled with the reference numeral 10 at the bottom right.</p>	<p style="text-align: right;">10</p>

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

Use of Metal Foams in Armor Systems

BACKGROUND OF THE INVENTION

FIELD OF THE INVENTION

This invention relates generally to armor systems for structural protection
5 against ballistic impact or explosive blast, and more particularly to the use of a
metallic foam as the shock energy-absorbing element in a multi-layer armor system.

DESCRIPTION OF THE RELATED ART

With increasing terroristic violence and military action, there is a need for
improved structural protection against ballistic impact from projectiles or blast
10 protection from explosives. Such structural protection can be built into the
infrastructure of a building to reinforce the building, or certain rooms within a
building, against attack. Structural protection is also useful in vehicles, illustratively
military vehicles, such as tanks, or civilian VIP vehicles. Presently, a multi-layer
armor system is employed in known vehicular applications.

15 A typical configuration for the armor system in medium weight military
vehicles, for example, consists of a high strength strike face (either a metal or a
ceramic plate), bonded to a ceramic tile, which is subsequently bonded to a metallic
backing plate. In this configuration, the ceramic tile breaks-up or deforms an
incoming projectile, and the metallic backing "catches" the extant penetrator and
20 ceramic fragments. The high strength strike plate aids the ceramic tile by providing
front face confinement, and may, in some cases, protect the ceramic tile from field
damage.

Upon projectile impact at typical ordnance velocities, a stress wave is
generated and propagates through the ceramic tile. Reflections from boundaries and
25 subsequent stress wave interactions result in tensile stress states and attendant
microcracking. Microcracking due to these impact-induced stress waves weakens the
ceramic tile, allowing a projectile to penetrate more easily. In armor system designs
utilizing a metal strike plate over ceramic tile, stress waves from a projectile impact
on the metal strike plate can run ahead into the ceramic, and failure may initiate prior

to contact of the projectile with the ceramic tile. There is, therefore, a need for an armor system having an improved shock-absorbing element, and more particularly, a shock-absorbing element that gives more control of behind-the-target effects, such as backface deformation and spalling.

5 Metallic foams with a high fraction of porosity are a new class of materials which have attributes that lend themselves to various engineering applications, including sound and heat isolation, lightweight construction, and energy absorption. The latter two applications, in particular, make use of the unique characteristics of a metallic cellular material, specifically the combination of its comparatively high
10 specific strength and its characteristic non-linear deformation behavior. As will be described more completely hereinbelow, certain metal foams are effective in containing rearward deformation of a target under high-speed impact, and therefore are useful in controlling backface deformation and spalling. Moreover, metal foams are capable of mitigating impact-induced stress waves thereby delaying damage to
15 ceramic layers in armor systems employing same.

It is, therefore, an object of the invention to provide an armor system incorporating metal foam as a shock energy-absorbing element to improve protection of equipment and personnel behind the target.

It is a further object of the invention to provide an armor system incorporating
20 metal foam as a shock energy-absorbing element to control behind-the-target effects as a result of backface deformation caused by the high energy impact of a projectile.

Summary of the Invention

The foregoing and other objects, features and advantages are achieved by this invention which provides a metallic foam as a shock-absorbing element in a multi-
25 layer armor system. In preferred embodiments, the metallic foam has a closed-cell pore structure and a high fraction of porosity, preferably ranging from about 50-98 percent by volume.

Metallic foams useful in the practice of the present invention may be, but are not limited to, metal foams of aluminum, steel, lead, zinc, titanium, nickel and alloys or metal matrix composites thereof. Metal foams can be fabricated by various processes that are known for the manufacture of metal foams, including casting, powder metallurgy, metallic deposition, and sputter deposition. Exemplary processes for making metal foams are set forth in U.S. Patent Nos. 5,151,246; 4,973,358; and 5,181,549, the text of which is incorporated herein by reference.

U.S. Patent 5,151,246, for example, describes a powder metallurgy process for making foamable materials using metallic powders and small amounts of propellants. The process starts by mixing commercially available metal powder(s) with a small amount of foaming agent. After the foaming agent is uniformly distributed within the matrix material, the mixture is compacted to yield a dense, semi-finished product without any residual open porosity. Further shaping of the foamable material can be achieved through subsequent metalworking processes such as rolling, swaging or extrusion.

Following the metalworking steps, the foamable material is heated to temperatures near the melting point of the matrix metal(s). During heating, the foaming agent decomposes, and the released gas forces the densified material to expand into a highly porous structure. The density of the metal foams can be controlled by adjusting the content of the foaming agent and several other foaming parameters, such as temperature and heating rate. The density of aluminum foams, for example, typically ranges from about 0.5 to 1 g/cm³.

Strength, and other properties of foamed metals can be tailored by adjusting the specific weight (or porosity), alloy composition, heat treatment history, and pore morphology as is known to those of skill in the art. In advantageous embodiments, the metallic foam will have high mechanical strength.

Metal foams are easily processed into any desired shape or configuration by conventional techniques, such as sawing drilling, milling, and the like. Moreover,

metal foams can be joined by known techniques, such as adhesive bonding, soldering, and welding.

In certain preferred embodiments of the invention, the shock-absorbing element is closed-cell aluminum foam, and in a specific illustrative embodiment, the shock-absorbing element is closed-cell aluminum foam with a porosity of 80 percent by volume.

In device embodiments of the present invention, a multi-layered armor system, suitable for structural protection against ballistic impact or explosive blast, such as armor systems used in connection with military armored vehicles, includes one or more layers of a metal foam as a shock energy-absorbing element.

As used herein, the term "multi-layer armor system" means at least two plates of metal, metal foam, ceramic, plastic, and the like, known or developed, for defense or protection systems. In the present invention, the multi-layer armor system includes at least a strike plate, or buffer plate, bonded or otherwise held in communication with, a shock-absorbing element that is a layer of metallic foam.

As described hereinabove, the metallic foam preferably has a closed-cell pore structure and a high fraction of porosity. Illustratively, the metallic foam may be aluminum, steel, lead, zinc, titanium, nickel and alloys or metal matrix composites thereof, with porosity ranging from about 50-98 percent by volume. In a particularly preferred embodiment of the invention, the metallic foam is a closed-cell aluminum foam having a porosity of 80 percent by volume.

The term "strike plate" refers to a high strength metal or ceramic plate that has a front face surface that would receive the initial impact of a projectile or blast. The back surface of the strike plate is adjacent to a first surface of the shock-absorbing element that, in the present invention, is a sheet or layer of metallic foam. It is to be understood that the term "strike plate," as used herein, refers to any buffer plate of a high strength material that receives impact or impact-induced stress waves prior to a shock-absorbing element.

The strike plate may be a flat sheet of a high strength metal, ceramic or polymer-based composite, such as a fiber-reinforced polymer composite.

In a preferred embodiment, the multi-layer armor system of the present invention further includes a deformable backing plate bonded to, or otherwise held in communication with, a face surface of the metallic foam sheet or layer opposite, or distal, to the surface contiguous to the strike plate. The backing plate illustratively is a sheet of a deformable metal, such as titanium, aluminum, or steel.

In a specific illustrative embodiment of a multi-layer armor system in accordance with the invention, a shock-absorbing layer of metallic foam is sandwiched between a high strength strike plate and a deformable backing plate. Of course, the multi-layered armor system may comprise additional elements, in any sequence, and the embodiments presented herein are solely for the purposes of illustrating the principles of the invention.

BRIEF DESCRIPTION OF THE DRAWING

Comprehension of the invention is facilitated by reading the following detailed description, in conjunction with the annexed drawing, in which:

Fig. 1 is a schematic representation of an illustrative armor system incorporating metallic foam as a shock energy-absorbing element in accordance with the principles of the present invention;

Fig. 2 is a photomicrograph of a high porosity, closed-cell aluminum foam showing the typical microstructure in cross-section;

Fig. 3 is a graphical representation of the typical behavior of a metal foam, of the type shown in Fig. 2, under a uniaxial load; and

Fig. 4 is photomicrograph of the aluminum foam of Fig. 2 showing a cross-sectional view of the microstructure following deformation by high energy impact.

DETAILED DESCRIPTION OF THE INVENTION

Fig. 1 is an illustrative schematic representation of an improved armor system 10 of the type having a high strength strike plate 11, at least one shock energy-absorbing element 12, and a backing plate 13. In the embodiment of Fig. 1, a closed-cell metal foam is used as shock energy-absorbing element 12. High strength strike plate 11 may be ceramic or metal. Backing plate 13 is typically a highly deforming metal, such as titanium, aluminum, or steel. However, backing plate 13 may comprise one or more layers of metal and/or ceramic, as well as polymer-based composites. In armor system 10, the closed-cell metal foam is effective in containing rearward deformation of the strike plate 11 in a ballistic target structure. The metal foam has the ability to control backface deformation, without sacrificing ballistic efficiency behind targets with highly deforming back plates, via a mechanism that will be discussed more completely hereinbelow.

The shock energy-absorbing element 12 preferably comprises a closed-cell metallic foam which, illustratively, may be aluminum, steel, lead, zinc, titanium, nickel, and alloys or metal matrix composites thereof. Preferred metal foams have a high fraction of porosity, typically ranging from about 50-98 by volume percent. In a specific preferred embodiment, shock energy-absorbing element 12 is a closed-cell aluminum foam having a porosity of 80 by volume. Fig. 2 shows the microstructure (*i.e.*, the pore structure) of this particular aluminum foam material.

This type of pore structure provides a substantial increase in the stiffness/weight ratio (SWR) of the material with a low fractional density. Under deformation, this microstructure features localized cell collapse and rapid compaction energy dissipation, which leads to unique deformation behaviors and material properties including high SWR and energy absorption in the material.

During deformation, metal foams of the type shown in Fig. 2, exhibit the universal deformation behavior shown in Figure 3 as they move from the quasi-elastic regime to the plastic regime. Fig. 3 is a graphical representation of the behavior of the metal foam of Fig. 2 under uniaxial load referred to as a "loading curve." The

vertical axis of Fig. 3 represents stress and the horizontal axis represents strain. The loading curve of Fig. 3 is divided into three regions: linear elastic region 31, collapse region 32 (where plateau stress remains relatively constant) and densification region 33. In linear elastic region 31, the elastic portion of the stress-strain curve is only partially reversible. During loading, small-scale localized plastic deformation has already taken place within the sample. These small-scale plastic deformations also contribute to the mechanical damping of metal foams. In collapse region 32, the cell wall-buckling event occurs and the foam progressively collapses until densification region 33. The deformation in densification region 33 is highly localized and is preceded by the advance of a densification front from deformed to undeformed regions of the sample. For strain rate insensitive materials such as aluminum, the deformation behavior at the high strain rates remain the same. The area under the loading curve represents the deformation energy absorbed by the metal foam.

Metal foams can be fabricated to maximize the energy absorption capability by adjusting foam parameters including alloying elements, density level, cell size, wall thickness, and uniformity. Improvements in modulus and plateau stress via heat treatment of the metal foam, or via addition of particulate or whisker reinforcements to the metal foam, are additional techniques known to increase the energy absorption capability.

Metal foams are capable of mitigating the impact-induced stress waves from the strike plate, thereby delaying or eliminating damage to underlying layers, which in some embodiments might be a ceramic tile, and improving protection of the personnel and equipment behind the target. The deformation energy due to shock impact first densifies the front portion (in the loading direction) of the metal foam layer that forms the shock energy-absorbing element. Subsequent deformation introduces tearing and shearing of the cell walls, an effect of core shearing deformation for energy dissipation in the cellular structure. Thus, the deformation energy is redirected and dissipated sideways. This is best illustrated in Fig. 4 which is a cross-sectional view of the microstructure of the aluminum foam of Fig. 2

showing deformation following high energy impact. This type of deformation mechanism reduces the transmitted deformation energy behind the target in the loading direction. The energy of the impact-induced stress waves is also dissipated efficiently within the cellular network. The high degree of porosity in metal foam is beneficial for the absorption of the wave energy, and the cellular network generates the cavity effect for scattering the wave energy within the network.

The armor systems of the present invention would be useful as protection systems for ballistic impact and for blast. Moreover, while the illustrative embodiment presented herein is directed to a three element system, it is to be understood that invention contemplates the use of closed-cell, high strength metal foams having a high fraction of porosity, as a shock energy-absorbing element in any other configuration developed, or to be developed, wherein its ability to contain rearward deformation under high-speed impact, would be useful.

Although the invention has been described in terms of specific embodiments and applications, persons skilled in the art can, in light of this teaching, generate additional embodiments without exceeding the scope or departing from the spirit of the invention described herein. Accordingly, it is to be understood that the drawing and description in this disclosure are proffered to facilitate comprehension of the invention, and should not be construed to limit the scope thereof.

WHAT IS CLAIMED IS:

1. A shock energy-absorbing element for a multi-layer armor system comprising a metallic foam.

2. The shock energy-absorbing element for a multi-layer armor system of claim 1 wherein the metallic foam is a closed-cell metallic foam.

3. The shock energy-absorbing element for a multi-layer armor system of claim 2 wherein the metallic foam has a porosity ranging from about 50-98 percent by volume.

4. The shock energy-absorbing element for a multi-layer armor system of claim 3 wherein the metallic foam is a closed-cell metallic foam selected from the group consisting of aluminum, steel, lead, zinc, titanium, nickel, and alloys or metal matrix composites thereof.

5. The shock energy-absorbing element for a multi-layer armor system of claim 4 wherein the closed-cell metallic foam is a closed-cell aluminum foam.

6. The shock energy-absorbing element for a multi-layer armor system of claim 5 wherein the closed-cell aluminum foam has a porosity of 80 percent by volume.

7. A multi-layered armor system comprising at least one layer of a metallic foam as a shock energy-absorbing element.

8. The multi-layered armor system of claim 7 further comprising a strike plate on one surface of at least one layer of the at least one layer of metallic foam.

9. The multi-layered armor system of claim 8 further comprising a deformable backing plate on a surface of at least one layer of the at least one layer of metallic foam distal to the strike plate.

10. The multi-layered armor system of claim 7 wherein the shock energy-absorbing element comprises a closed-cell metallic foam.

11. The multi-layered armor system of claim 10 wherein the closed-cell metallic foam is selected from the group consisting of aluminum, steel, lead, zinc, titanium, nickel, and alloys or metal matrix composites thereof.

12. The multi-layered armor system of claim 11 where the porosity of the closed-cell metallic foam ranges from about 50-98 percent by volume.

13. A multi-layered armor system comprising a shock-absorbing element of a metallic foam sandwiched between a strike plate and a deformable backing plate.

5 14. The multi-layered armor system of claim 13 wherein the strike plate is selected from the group consisting of high strength metals, ceramics, and polymer-based composites.

15. The multi-layered armor system of claim 13 wherein the shock energy-absorbing element comprises a closed-cell metallic foam.

10 16. The multi-layered armor system of claim 15 wherein the closed-cell metallic foam is selected from the group consisting of aluminum, steel, lead, zinc, titanium, nickel and alloys or metal matrix composites thereof.

17. The multi-layered armor system of claim 16 where the porosity of the closed-cell metallic foam ranges from about 50-98 percent by volume.

15 18. The multi-layered armor system of claim 13 wherein the deformable backing plate comprises a metal selected from the group consisting of titanium, aluminum, and steel.

1/2

FIG. 1






FIG. 3




2/2

FIG. 2



1 CM

FIG. 4



2 CM

INTERNATIONAL SEARCH REPORT

Int. l. Application No

PCT/US 00/06220

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 F41H5/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 F41H

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 20 39 343 A (DORNIER SYSTEM GMBH) 10 February 1972 (1972-02-10) claims 1,2; figure page 2, paragraph 2 -page 3, paragraph 2	1,7-9, 13,14,18
Y		10-12, 15-17
A	DE 90 07 336 U (NEUERO STAHLBAU GMBH & CO) 4 July 1991 (1991-07-04) claim; figure 2 --- -/--	8,9,13, 14,18

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

° Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

4 August 2000

Date of mailing of the international search report

10/08/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Schwingerl, D

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 00/06220

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 151 246 A (BAUMEISTER JOACHIM ET AL) 29 September 1992 (1992-09-29) cited in the application abstract; figure 3 column 4, line 48 - line 50 column 5, line 53 - line 61 column 7, line 34 - line 42	1-6
Y		10-12, 15-17
X	US 4 973 358 A (JIN ILJOUN ET AL) 27 November 1990 (1990-11-27) cited in the application table 1 column 1, line 11 - line 14 column 1, line 34 - line 52 column 3, line 40 - line 66 column 2, line 16 - line 19	1-6
A		4, 11, 16
X	US 5 181 549 A (SHAPOVALOV VLADIMIR I) 26 January 1993 (1993-01-26) cited in the application abstract; claim 10; figure 3 column 1, line 7 - line 12 column 6, line 62 - line 68	1-6
A		4, 11, 16
A	US 3 604 374 A (MATSON HAROLD E ET AL) 14 September 1971 (1971-09-14) figures 3, 3A column 2, line 32 - column 3, line 17	8, 9, 13, 14, 18

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 00/06220

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 2039343	A	10-02-1972	FR 2103981 A	14-04-1972
DE 9007336	U	04-07-1991	NONE	
US 5151246	A	29-09-1992	DE 4018360 C	29-05-1991
			DE 4101630 A	12-12-1991
			AT 142135 T	15-09-1996
			CA 2044120 A	09-12-1991
			DE 59108133 D	10-10-1996
			EP 0460392 A	11-12-1991
			JP 2898437 B	02-06-1999
			JP 4231403 A	20-08-1992
			DE 4124591 C	11-02-1993
US 4973358	A	27-11-1990	AU 6287690 A	08-04-1991
			BR 9007633 A	07-07-1992
			CA 2066421 A,C	07-03-1991
			WO 9103578 A	21-03-1991
			EP 0490918 A	24-06-1992
			JP 5500391 T	28-01-1993
			MX 172441 B	16-12-1993
			NO 920869 A	05-05-1992
			US 5112697 A	12-05-1992
			US 5221324 A	22-06-1993
			ZA 9007015 A	30-10-1991
US 5181549	A	26-01-1993	AU 2184492 A	21-12-1992
			EP 0583415 A	23-02-1994
			WO 9219400 A	12-11-1992
US 3604374	A	14-09-1971	NONE	